


Ælement Fusion for ANSI mortise locks Outdoor Version




The Ælement Fusion's small, customizable light ring reader offers a discreet electronic lock for any type of building looking to deploy electronic access control with a stylish, yet technologically-advanced solution. Salto offers a variety of door handles and finishes to complement any door style. The Ælement Fusion ANSI version is specially designed to fit on ANSI standards profile doors.



4-15/16" max.
(125mm) 最多
최대

1 1/16" min.
(17mm) 最少
최소

2-1/8" max.
(55mm) 最多
최대



1-3/4" (45mm) <Door thickness<4-15/16" (125mm).
1-3/4" (45mm) <Épaisseur d' porte<4-15/16" (125mm).
1-3/4" (45mm) <Espesor de puerta<4-15/16" (125mm).
1-3/4" (45mm) <門厚度<4-15/16" (125mm).
1-3/4" (45mm) <문 간격<4-15/16" (125mm).


Only SALTO spindle.
Seulement carrés SALTO.
Solo cuadradillos SALTO.
只限SALTO的轴。
SALTO 스펀들만.

Lock and control must be aligned.
La serrure et le contrôleur doivent être alignés.
Cerradura y control alineados.
螺栓 (取决于门的厚度)
잠금 및 제어기가 정렬되어야 합니다.



AF ixx.. E series

Ø1-25/32"
(Ø45mm)




OUTSIDE
EXTÉRIEUR
EXTERIOR
外側
외부




INSIDE
INTÉRIEUR
INTERIOR
内側
내부


AF ixx..E series

OUTSIDE ONLY



BOLT (Depending
on door thickness)
螺栓 (取决于门的厚度)
BOLT (추가 문 간격에)





****Depending on the model, Mortise Lock may not be included.**

****Selon le modèle, la serrure à mortaiser peut ne pas être incluse.**

****Dependiendo del modelo, la cerradura de embutir puede no estar incluida.**

****모델에 따라 모티스 잠금 장치가 포함되지 않을 수 있습니다.**

****視型號而定，暗鎖可能不包含在內。**

SALTO ANSI Locks
SALTO ANSI Serrures
Cerraduras ANSI SALTO
SALTO ANSI 插芯锁
SALTO ANSI 잠금

For more information



CLICK HERE


For door preparation see: 221373 or 4DS00020.
Pour préparation de la porte, voir: 221373 ou 4DS00020.
Para mecanizado de puerta, ver: 221373 ó 4DS00020.
有关门的准备，请看：221373-4DS00020。
문 준비를 위해: 221373 또는 4DS00020 를 보십시오.

The mounting with other spindles voids the guarantee.
Le montage d'autres carrés annulera le garantie.
El montaje de otros cuadradillos anula la garantía.
与其他轴安装在一起，则保修无效。
다른 스펀들과 함께 장착하면 보증이 무효화됩니다.


NOTE: Screws and spindles are included in the box of the reader.
NOTE: Les vis et les carrés sont inclus dans la boîte du lecteur.
NOTA: Los tornillos y cuadradillos están incluidos en la caja del lector.
注意：螺丝和把手是包含在读卡器的盒子里
참고: 나사와 스펀들은 리더의 상자에 포함되어 있습니다.

(*) Only for door thickness > 2-9/16" (65mm).
(*) Seulement pour portes de épaisseur > 2-9/16" (65mm).
(*) Solo para grosor de puerta > 2-9/16" (65mm).
(*) 只用于厚度超过2-9/16" (65mm) 的门
(*) 도어 두께만 > 2-9/16"(65mm)


1





2




3




METAL SURFACES




4



5



6




(Eng) Cable connection (F) Câble de raccordement (E) Conexión cableado (ZH) 电线连接 (KR) 케이블 연결




Select an option depending on the position of the reader (a or b).
Sélectionnez une option en fonction de la position du lecteur (a ou b).
Seleccionar una opción dependiendo de la posición del lector (a ó b).
根据读卡器的位置选择一个选项 (a或b)
리더의 위치(a 또는 b)에 따라 옵션을 선택합니다.


7a




7b




8a




8b




9a




9b




10




11



12



13



Eng

**AT THIS POINT DO NOT
CLOSE THE DOOR.
PROGRAM THE LOCK FIRST**

F

**NE FERMEZ PAS LA PORTE.
PROGRAMMEZ LA BÉQUILLE
AVANT**

E

**NO CIERRE LA PUERTA.
PROGRAME LA CERRADURA**

ZH


在这里，不要关门，先对锁进行编程

KR


**이때 문을 닫지 말고 먼저 잠금 장치를
프로그래밍하십시오.**

(Eng) Emergency opening (F) Ouverture d'urgence (E) Apertura emergenciac (ZH) 紧急开锁 (KR) 비상 개방



1



2



3



Eng Use and maintenance F L'utilisation et l'entretien E Uso y mantenimiento ZH 使用和维护 KR 사용 및 주요결속

Operating conditions: 0°C<t<60°C.

Condition de

fonctionnement: 0°C<t<60°C.

Condiciones de funcionamiento:

0°C<t<60°C.

操作条件: 0°C<t<60°C.

작동 조건: 0°C<t<60°C.

To use in non condensing environments.

Pour des environnement sans condensation.

Para uso en entornos sin condensación.

在非冷凝环境中使用.

비 응축 환경에서 사용.

Eng Battery change F Remplacer les piles E Cambio de pilas ZH 更换电池 KR 배터리 교체

